



**CUMMINS INC.**  
Columbus, IN 47201  
Marine Performance Curves

Basic Engine Model  
**QSM11-M**

Curve Number:  
**M-20105**


Engine Configuration  
**D353013MX03**

CPL Code:  
**PP8753**

Date:  
**12-May-10**

Displacement: **10.8 liter [661 in³]**      Rated Power: **449 kw [602 bhp, 610 mhp]**  
 Bore: **125 mm [4.92 in]**              Rated Speed: **2300 rpm**  
 Stroke: **147 mm [5.79 in]**              Rating Type: **Intermittent Duty**  
 Fuel System: **CELECT**                  Aspiration: **Turbocharged / Sea Water Aftercooled**  
 Cylinders: **6**

CERTIFIED: This diesel engine complies with or is certified to the following agencies requirements:  
 IMO Tier I - Tier 1 (One) NOx requirements of International Maritime Organization (IMO), MARPOL 73/78 Annex VI, Regulation 13  
 EPA Tier 2 - Model year requirements of the EPA marine regulation (40CFR94)



Speed	Full Throttle- Power		Full Throttle- Torque		Fuel Cons.- Prop. Curve 2.7 Exp.	
	rpm	kw (hp)	N·m (ft·lb)	L/hr (gal/hr)		
2340	449	(602)	1832	(1351)		
2300	449	(602)	1864	(1375)	116.6	(30.8)
2200	436	(584)	1891	(1395)	97.5	(25.7)
2000	415	(556)	1979	(1460)	72.7	(19.2)
1900	403	(541)	2027	(1495)	63.3	(16.7)
1800	391	(524)	2074	(1530)	55.1	(14.6)
1600	348	(466)	2074	(1530)	41.9	(11.1)
1500	314	(421)	2000	(1475)	35.5	(9.4)
1400	278	(373)	1898	(1400)	29.4	(7.8)
1200	208	(279)	1654	(1220)	18.8	(5.0)
1100	180	(241)	1559	(1150)	15.9	(4.2)
1000	143	(192)	1369	(1010)	12.2	(3.2)
900	109	(147)	1159	(855)	9.2	(2.4)
800	80	(107)	956	(705)	7.0	(1.8)

\* Cummins Full Throttle Requirements:

- Engine achieves or exceeds rated rpm at full throttle under any steady operating condition
- Engines in variable displacement boats (such as pushboats, tugboats, net dragners, etc.) achieve no less than 100 rpm below rated speed at full throttle during a dead push or bollard pull
- Engine achieves or exceeds rated rpm when accelerating from idle to full throttle

Rated Conditions: Ratings are based upon ISO 15550 reference conditions; air pressure of 100 kPa [29.612 in Hg], air temperature 25deg. C [77 deg. F] and 30% relative humidity. Power is in accordance with IMCI procedure. Member NMMA. Unless otherwise specified, tolerance on all values is +/-5%.

Full Throttle curve represents power at the crankshaft for mature gross engine performance corrected in accordance with ISO 15550. Propeller Curve represents approximate power demand from a typical propeller. Propeller Shaft Power is approximately 3% less than rated crankshaft power after typical reverse/reduction gear losses and may vary depending on the type of gear or propulsion system used.

Fuel Consumption is based on fuel of 35 deg. API gravity at 16 deg C [60 deg. F] having LHV of 42,780 kJ/kg [18390 Btu/lb] and weighing 838.9 g/liter [7.001 lb/U.S. gal].

Intermittent Duty (INT): Intended for intermittent use in variable load applications where full power is limited to two hours out of every eight hours of operation. Also, reduced power operations must be at or below 200 rpm of the maximum rated rpm. This rating is an ISO 15550 fuel stop power rating and is for applications that operate less than 1,500 hours per year.

CHIEF ENGINEER

# Propulsion Marine Engine Performance Data

**Curve No.** M-20105  
**DS :** 3075  
**CPL :** PP8753  
**DATE:** 12-May-10

## General Engine Data

Engine Model .....	QSM11-M
Rating Type .....	Intermittent Duty
Rated Engine Power .....	449 [602] kW [hp]
Rated Engine Speed .....	2300 rpm
Rated Power Production Tolerance .....	±% 5
Rated Engine Torque .....	1864 [1375] N-m [lb-ft]
Peak Engine Torque @ 1700 rpm.....	2135 [1575] N-m [lb-ft]
Brake Mean Effective Pressure .....	2164 [314] kPa [psi]
Indicated Mean Effective Pressure.....	2405 [349] kPa [psi]
Maximum Allowable Engine Speed .....	2360 rpm
Maximum Torque Capacity from Front of Crank <sup>2</sup> .....	0 [0] N-m [lb-ft]
Compression Ratio .....	16.3:1
Piston Speed .....	11.3 [2219] m/sec [ft/min]
Firing Order .....	1-5-3-6-2-4
Weight (Dry) - Engine Only - Average .....	N.A. [N.A.] kg [lb]
Weight (Dry) - Engine With Heat Exchanger System - Average.....	1188 [2620] kg [lb]
Weight Tolerance (Dry) Engine Only .....	N.A. 3xStd Dev (±%)

## Governor Settings

High Speed Governor Break Point.....	2340 rpm
Minimum Idle Speed Setting .....	600 rpm
Normal Idle Speed Variation .....	±rpm 10
High Idle Speed Range Minimum .....	2340 rpm
Maximum .....	2360 rpm

## Noise and Vibration

Average Noise Level - Top	(Idle)..	dBa @ 1m	TBD
	(Rated) .....	dBa @ 1m	TBD
Average Noise Level - Right Side	(Idle)..	dBa @ 1m	TBD
	(Rated) .....	dBa @ 1m	TBD
Average Noise Level - Left Side	(Idle)..	dBa @ 1m	TBD
	(Rated) .....	dBa @ 1m	TBD
Average Noise Level - Front	(Idle)..	dBa @ 1m	TBD
	(Rated) .....	dBa @ 1m	TBD

## Fuel System<sup>1</sup>

Avg. Fuel Consumption - ISO 8178 E3 Standard Test Cycle .....	76.1 [20.1] l/hr [gal/hr]
Avg. Fuel Consumption - ISO 8178 E5 Standard Test Cycle .....	39.2 [10.4] l/hr [gal/hr]
Fuel Consumption at Rated Speed .....	116.6 [30.8] l/hr [gal/hr]
Approximate Fuel Flow to Pump .....	280.1 [74.0] l/hr [gal/hr]
Maximum Allowable Fuel Supply to Pump Temperature .....	60.0 [140] °C [°F]
Approximate Fuel Flow Return to Tank .....	163.5 [43.2] l/hr [gal/hr]
Approximate Fuel Return to Tank Temperature .....	93.4 [200] °C [°F]
Maximum Heat Rejection to Drain Fuel .....	4.5 [255] kW [Btu/min]
Fuel Transfer Pump Pressure Range.....	N.A. kPa [psi]
Fuel Pressure - Pump Out/Rail . Mechanical Gauge .....	1151 [167] kPa [psi]
INSITE Reading .....	N.A. kPa [psi]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

- <sup>1</sup> Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.
- <sup>2</sup> No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.
- <sup>3</sup> Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.
- <sup>4</sup> Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.
- <sup>5</sup> May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS ENGINE COMPANY, INC  
 COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://cmdmarine.com/>

# Propulsion Marine Engine Performance Data

**Curve No.** M-20105  
**DS :** 3075  
**CPL :** PP8753  
**DATE:** 12-May-10

## Air System<sup>1</sup>

Intake Manifold Pressure .....	kPa [in Hg]	280 [83]
Intake Air Flow .....	l/sec [cfm]	678 [1436]
Heat Rejection to Ambient .....	kW [Btu/min]	35 [1996]

## Exhaust System<sup>1</sup>

Exhaust Gas Flow .....	l/sec [cfm]	1549 [3283]
Exhaust Gas Temperature (Turbine Out) .....	°C [°F]	496 [924]
Exhaust Gas Temperature (Manifold) .....	°C [°F]	661 [1220]

## Emissions (in accordance with ISO 8178 Cycle E3)

NOx (Oxides of Nitrogen) .....	g/kw-hr [g/hp-hr]	4.45 [3.32]
HC (Hydrocarbons) .....	g/kw-hr [g/hp-hr]	0.22 [0.16]
CO (Carbon Monoxide) .....	g/kw-hr [g/hp-hr]	0.37 [0.27]
PM (Particulate Matter) .....	g/kw-hr [g/hp-hr]	0.09 [0.07]

## Emissions (in accordance with ISO 8178 Cycle E5)

NOx (Oxides of Nitrogen) .....	g/kw-hr [g/hp-hr]	4.46 [3.33]
HC (Hydrocarbons) .....	g/kw-hr [g/hp-hr]	0.25 [0.19]
CO (Carbon Monoxide) .....	g/kw-hr [g/hp-hr]	0.45 [0.33]
PM (Particulate Matter) .....	g/kw-hr [g/hp-hr]	0.10 [0.08]

## Cooling System<sup>1</sup>

Sea Water Pump Specifications .....	MAB 0.08.17-07/16/2001	
Pressure Cap Rating (With Heat Exchanger Option) .....	kPa [psi]	103 [15]

## Engines without Low Temperature Aftercooling (LTA )

### Sea Water Aftercooled Engine (SWAC)

Coolant Flow to Engine Heat Exchanger .....	l/min [gal/min]	N.A. [N.A.]
Standard Thermostat Operating Range (Start to Open) .....	°C [°F]	71 [160]
Standard Thermostat Operating Range (Full Open) .....	°C [°F]	80 [175]
Heat Rejection to Engine Coolant <sup>3</sup> .....	kW [Btu/min]	139 [7915]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

- <sup>1</sup> Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.
- <sup>2</sup> No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.
- <sup>3</sup> Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.
- <sup>4</sup> Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.
- <sup>5</sup> May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS ENGINE COMPANY, INC  
 COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://cmdmarine.com/>